

PLYWOOD CARE AND MAINTENANCE

Looking after your premium grade architectural plywood

ABOUT YOUR PREMIUM PRODUCT

Your plywood is a low VOC, low E0 panel uniquely sourced from Australian Certified, environmentally sustainable mills and is 100% renewable. Every sheet is different and unique. No one sheet will look the same as this is a natural product so you will see colour variation batch to batch, you may also see all the imperfections that make timber perfect such as small pin knots, light to strong grain swirls and timber cracks all evident and naturally occurring in timber veneers.

DELIVERY

- ❖ Check your order and ensure the correct product and quantities are received.
- ❖ Note any transport damage or issues on the con note when goods are received and email it to: info@stackpanel.com.au prior to cutting/finishing other work starting on the material within 24 hours of delivery.

INSTALLATION

Carefully select the panels that best meet the customers expectations ie. grain and colour for installation in the more prominent areas.

shade and variation occurs as inipanel is a natural timber so there will be slight changes with each batch, samples may differ from the delivered product slightly. Follow the appropriate installation guides and procedures, the team at tack Panel are always ready to help, so if you do have any questions feel free to email us info@stackpanel.com.au.

U N N D P C N N N

Claims will not be accepted once anything occurs to alter the original product.

- n Claims for incorrect quantities must be made within 5 business days of the order being delivered.
- n Claims will only be recognised if the original product has not been altered and is in re-saleable condition at the discretion of Stack Panel.
- n Should you wish to make a claim, please supply the following information to info@stackpanel.com.au:
 - i Photos of the product (face and back)
 - i Invoice number
 - i Date of delivery

PRE-APPLICATION

- ❖ Ensure plywood is stored evenly weighted down flat position inside, away from external elements and kept moisture and dust free.
- ❖ Place plywood in the area it will be installed to for observation at various times of the day, and from different viewpoints to ensure product meets your expectations. Then re-stack to ensure sheets stay flat.
Plywood is fragile, please take care so no edges are knocked or faces are scratched when handling the product.

LOOKING AFTER YOUR PLYWOOD

- ❖ Protect your product by not exposing it to moisture or direct sunlight, it will yellow over time naturally.
- ❖ Use mild damp rags to wipe the surface if there are stains, no high pressure cleaning.
- ❖ Check the finish recommendations, if raw, do not use oil based finishes on the product. Plywood will bow if not stored flat, do not use plywood in free-standing door applications, it must be fixed at all times to prevent bowing.

STACK
PANEL